

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1. (Cancelled)

2. (Currently Amended) The ~~diagnostic control~~ system of claim ~~[[1]]~~15, wherein said diagnostic module monitors ~~and compares~~ at least one of the following conditions:

said valve position of said electronic stepper regulator;

an error value percentage indicative of the percentage of sampled error within an accepted offset range for a defined period of time;

a moving average of said valve position for a defined period of time;

a steady state loading percentage set equal to said moving average of said valve position for a defined period of time when said error value percentage is less than fifty percent;

a discharge cooling fluid temperature;

an evaporator coil inlet temperature;

an evaporator coil exit temperature;

a moving average of a difference between said discharge cooling fluid temperature and said evaporator coil inlet temperature;

a moving average of a difference between said evaporator coil exit temperature and said evaporator coil inlet temperature to approximate a superheat value; and

a length of time said evaporator coil exit temperature is less than said evaporator coil inlet temperature during a predefined period of time.

3. (Currently Amended) The ~~diagnostic~~-control system of claim ~~[[1]]15~~, wherein said ~~diagnostic~~-module monitors a percentage of sampled error over a defined period of time.

4. (Currently Amended) The ~~diagnostic~~-control system of claim 3, wherein said predetermined ~~fault~~-value is an accepted offset range.

5. (Currently Amended) The ~~diagnostic~~-control system of claim 4, wherein said ~~diagnostic~~-module determines an error value percentage indicative of said percentage of sampled error within said accepted offset range for said defined period of time.

6. (Cancelled)

7. (Currently Amended) The ~~diagnostic~~-control system of claim ~~[[6]]27~~, wherein said alert module issues an alert signal when said ~~a~~-valve position of said electronic stepper regulator valve is approximately zero percent for approximately ninety percent of said defined period of time and said error value percentage is less than one hundred percent, said alert signal indicating said electronic stepper regulator valve is over-sized.

8. (Currently Amended) The ~~diagnostic-control~~ system of claim ~~[[6]]~~27, wherein said diagnostic module further monitors and compares a superheat value indicative of evaporator superheat.

9. (Currently Amended) The ~~diagnostic-control~~ system of claim 8, wherein said alert module issues an alert signal when said valve position of said electronic stepper regulator valve is approximately one hundred percent for approximately ninety percent of said defined period of time, said error value percentage is approximately zero percent, and said superheat value is approximately greater than 5°F, said alert signal indicating said electronic stepper regulator valve is undersized.

10. (Currently Amended) The ~~diagnostic-control~~ system of claim 8, wherein said diagnostic module further monitors and compares an evaporator coil inlet temperature value indicative of evaporator coil inlet temperature.

11. (Currently Amended) The ~~diagnostic-control~~ system of claim 10, wherein said alert module issues an alert signal when said error value percentage is approximately zero percent, said valve position of said electronic stepper regulator valve is approximately zero percent for approximately one hundred percent of said defined period of time, said evaporator coil inlet temperature value is less than approximately 32°F, and said superheat value is approximately greater than 5°F, said alert signal indicating said electronic stepper regulator valve is stuck open.

12. (Currently Amended) The ~~diagnostic-control~~ system of claim 10, wherein said error value percentage is approximately zero percent, said valve position of said electronic stepper regulator valve is approximately one hundred percent for approximately one hundred percent of said defined period of time, said evaporator coil inlet temperature value is approximately greater than 32°F, and said superheat value is approximately greater than 5°F, said alert signal indicating said electronic stepper regulator valve is stuck closed.

13. (Currently Amended) The ~~diagnostic-control~~ system of claim 10, wherein said diagnostic module further monitors and compares an evaporator coil exit temperature value indicative of evaporator coil exit temperature.

14. (Currently Amended) The ~~diagnostic-control~~ system of claim 13, wherein said alert module issues an alert signal when said valve position of said electronic stepper regulator valve is approximately one hundred percent for approximately one hundred percent of said defined period of time, said error value percentage is approximately zero, said superheat value is approximately less than 5°F, said evaporator coil inlet temperature value is approximately less than 25°F, and said evaporator coil exit temperature value is less than said evaporator coil inlet temperature value for greater than fifty percent of said defined period of time, said alert signal indicating that air flow to an evaporator is blocked or evaporator fans are not operating properly.

15. (New) A control system comprising:  
a controller operable to produce a variable duty cycle control signal for controlling  
a cooling system device in which said duty cycle is a function of demand for cooling;  
and  
a module associated with said controller and operable to compare said duty cycle  
with a predetermined value indicative of a system condition and issue a signal when  
said duty cycle bears a predetermined relationship to said fault value.
16. (New) The control system of claim 15, wherein said cooling system  
device is selected from a group comprising: an expansion device, a fan, a compressor,  
and a refrigerant control device.
17. (New) The control system of claim 16, wherein said expansion device is  
at least one of an orifice, thermal expansion valve, and electronic expansion valve.
18. (New) The control system of claim 16, wherein said refrigerant control  
device is an evaporator stepper regulator.
19. (New) The control system of claim 16, wherein said fan is a variable  
speed fan.
20. (New) The control system of claim 16, wherein said fan is a condenser  
fan.

21. (New) The control system of claim 20, wherein said condenser fan is a variable speed fan.

22. (New) The control system of claim 15, wherein said module includes a diagnostic module and an alert module.

23. (New) The control system of claim 22, wherein said diagnostic module compares said duty cycle with said predetermined value.

24. (New) The control system of claim 22, wherein said alert module issues said signal.

25. (New) The control system of claim 15, wherein said predetermined value is a fault value.

26. (New) The control system of claim 15, wherein said signal is an alert signal.

27. (New) The control system of claim 5, wherein said cooling system device is an evaporator stepper regulator and said module includes a diagnostic module and an alert module, said diagnostic module comparing said duty cycle with said predetermined value, and said alert module issuing said signal, said predetermined value being a fault value and said signal being an alert signal.